


Silencers

0674


Polymer Silencer, Male BSPP and Metric Thread



C	Code	E	G	H	kg
M5x0.8	0674 00 19	4	6.5	23	0.003
G1/8	0674 00 10	6	12.5	34	0.002
G1/4	0674 00 13	7	15.5	42.5	0.003
G3/8	0674 00 17	11.5	18.5	67.5	0.007
G1/2	0674 00 21	11	23.5	78	0.010
G3/4	0674 00 27	15.5	38.5	131	0.035
G1	0674 00 34	19.5	49	160	0.056

0676


Flow Control Polymer Silencer, Male BSPP and Metric Thread



C	Code	F	F1	G	H	H1	kg
M5x0.8	0676 00 19	8	1.5	9.2	16	11	0.008
G1/8	0676 00 10	13	2.5	15	20.5	14.5	0.003
G1/4	0676 00 13	15	4	18	29	22	0.007
G3/8	0676 00 17	20	6	24	38	30	0.018
G1/2	0676 00 21	25	8	30	50	40	0.045

0670


Threaded Silencer, Male BSPP Thread



C	Code	G	J	L	L1	kg
G1/8	0670 00 10	12	7	22	17	0.007
G1/4	0670 00 13	15	9	27	21	0.015
G3/8	0670 00 17	19	11	35	28	0.028
G1/2	0670 00 21	23	13	43	34	0.049
G3/4	0670 00 27	30	17	55	45	0.091
G1	0670 00 34	37	21	65	53	0.152

0673


Compact Silencer, Male BSPP and Metric Thread



C	Code	E	F	H	kg
M5x0.8	0673 00 19	4	7	8	0.001
G1/8	0673 00 10	8	14	14	0.008
G1/4	0673 00 13	8	17	14	0.012
G3/8	0673 00 17	10	22	18	0.020
G1/2	0673 00 21	12	27	21	0.042

0675

Threaded Silencer, Male BSPP and Metric Thread



C	Code	F	L	L1	kg
M5x0.8	0675 00 19	7	16	12	0.002
M7x1	0675 00 55	11	25	19	0.005
G1/8	0675 00 10	14	42	34	0.014
G1/4	0675 00 13	17	52	44	0.022
G3/8	0675 00 17	22	54	44	0.037
G1/2	0675 00 21	27	65	53	0.072


Silencers

0671

Push-In Silencer



Sintered bronze, nickel-plated brass




ØD	C	G	L	L1	kg
4	0671 04 00	13	41.5	24.5	0.015
6	0671 06 00	15	48	29	0.024
8	0671 08 00	15	49.5	29.5	0.025
10	0671 10 00	19.5	68	43.5	0.052
12	0671 12 00	20	68.5	43	0.052

0677

Miniature Silencer, Male BSPP Thread



Brass




C	C	G	H	kg
G1/8	0677 00 10	6	6	0.002
G1/4	0677 00 13	8	6	0.003
G3/8	0677 00 17	11	7	0.006
G1/2	0677 00 21	14	8	0.010
G3/4	0677 00 27	19	11	0.019
G1	0677 00 34	25	10	0.025

0672

Flow Control Silencer, Male BSPP Thread



Sintered bronze, nickel-plated brass




C	C	E	F	G	H	kg
		min		max		
G1/8	0672 00 10	8	14	14	17	0.017
G1/4	0672 00 13	8	17	17	20	0.029
G3/8	0672 00 17	10	22	22	20	0.058
G1/2	0672 00 21	12	27	27	28	0.094

0682

Compact Silencer, Male BSPP Thread



Stainless steel 316L




C	C	E	F	G	H	kg
G1/8	0682 00 10	8	7	14	15	0.007
G1/4	0682 00 13	8	7	17	15	0.011
G3/8	0682 00 17	10	8	22	18	0.019
G1/2	0682 00 21	12	10	27	22	0.038
G3/4	0682 00 27	15	12	32	27	0.063
G1	0682 00 34	18	14	38	32	0.117

0683

Compact Silencer, Male NPT Thread



Stainless steel 316L



C	C	E	F	G	H	kg
NPT1/8	0683 00 11	7	7	14	14	0.007
NPT1/4	0683 00 14	11	7	17	18	0.014
NPT3/8	0683 00 18	11	8	22	19	0.021
NPT1/2	0683 00 22	15	10	27	25	0.043