

SF06 perma fluid grease

Fluid grease for rolling and plain bearings subject to high loads

Description

perma SF06 is a multi-purpose fluid grease based on mineral oil. It offers good water resistance and corrosion protection even at high temperatures.

perma SF06

- Good water resistance
- High wear protection
- Easy feedability

Application

perma SF06 is used for the operational lubrication of bearings, guides and seals in the steel industry. Due to its consistency this fluid grease is suitable for use in perma Lubrication Systems.

Packaging

- perma lubrication systems
- 400g cartridges on request (for pre-lubrication with manual grease gun)

Application notes

perma SF06 is a lubricant especially developed for the perma Lubrication Systems.

To ensure adequate metering and maintenance-free lubrication, this product is only available in an perma Lubrication System.

Sourcing reference

perma-tec GmbH & Co. KG
Hammelburger Str. 21
97717 Euerdorf/Germany
Tel. +49 (0) 9704-609 0
Fax +49 (0) 9704-609 3190
www.perma-tec.com

Shelf life

Shelf life is approx. 12 months if the product is stored in its unopened original container in a dry and frost-protected place.

Product data

Base oil	mineral oil
Thickener	Al-complex
Base oil viscosity, DIN 51562, at 40°C, mm ² /s	220
at 100°C, mm ² /s	19
Color	brown, transparent
Density, DIN 51757, at 20°C, g/cm ³ , approx.	0.88
Drop point, DIN ISO 2176, °C	> 210
Speed factor, (n x d _m), approx.	3,0 x 10 ⁵
Consistency, NLGI grade, DIN 51818	0
Service temperature range, °C	- 20 to 130