



Housing units PCJ20-TV-FA125.5 (Series PCJ..-TV-FA125.5)

four-hole, plastic housing, radial insert ball bearing with eccentric locking collar, with Corrotect® coating, P seals

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	20 mm
L	87 mm
U	41,5 mm
A	28 mm
A ₁	13,4 mm
A ₂	18 mm
B ₁	31 mm
d ₃	33 mm
max	
J	63,5 mm
N	11 mm
Q	1/4 - 28 UNF
V	63 mm
m	0,33 kg Mass
C _r	12800 N Basic dynamic load rating, radial
C _{0r}	6600 N Basic static load rating, radial
C _{0r}	10200 N Load carrying capacity of housing, radial
G	
	GEH.CJ04-TV Designation of housing
	GRAE20-NPP-B-FA107/125.5 Designation of bearing
	KASK04-S-G Bearing end cap, closed design. Each housing unit is supplied with an end cap.
	KASK04-S-R-NBR Bearing end caps for housing units, open design, with integral rotary shaft seal. Available by agreement.

RWDR04-R-NBR Back Seal components.
To be ordered separately.

