



# Plummer block housing units

## PASE40-TV-FA125.5 (Series PASE..-TV-FA125.5)

plastic housing, radial insert ball bearing with eccentric locking collar, with Corrotect® coating, P seals

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	40 mm
L	184 mm
H <sub>2</sub>	99 mm
A	54 mm
B <sub>1</sub>	43,8 mm
d <sub>3</sub> max	58 mm
H	49,2 mm
H <sub>1</sub>	19,5 mm
J	137 mm
N	14 mm
N <sub>1</sub>	18 mm
Q	1/4 - 28 UNF
S <sub>1</sub>	32,8 mm
m	1,06 kg Mass
C <sub>r</sub>	32500 N Basic dynamic load rating, radial
C <sub>0r</sub>	19800 N Basic static load rating, radial
C <sub>0r</sub> G	11100 N Load carrying capacity of housing, radial
GEH.ASE08-TV Designation of housing	
GRAE40-NPP-B-FA107/125.5 Designation of bearing	

KASK08-S-G Bearing end cap, closed design.  
Each housing unit is supplied with an end cap.

KASK08-S-R-NBR Bearing end caps for housing units, open design, with integral rotary shaft seal.  
Available by agreement.

