



Stud type track rollers ZLE5205-2Z

(Series ZLE52..-2Z)

double row, eccentric stud, gap seals on both sides

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

D	62 mm
d _e	24 mm
B	88 mm
B ₁ max	32 mm
B ₂	56 mm
B _e	25 mm
C	20,6 mm
C ₁	8 mm
d ₂	30 mm
e	1 mm
G	M20X1,5
g	M8X1
l _G min	28 mm
l _g	8 mm
R	500 mm Curvature radius
r _{min}	1 mm
W	22 mm Nominal dimension for hexagonal socket
W ₁	17 mm
m	0,64 kg Mass
MA	150 Nm Nut tightening torque
C _r w	18800 N Effective dynamic load rating as track roller (radial)
C _{0r} w	13200 N Effective static load rating as track roller (radial)

Cur	670 N Fatigue limit load
w	
nD	6500 1/min Speed (with continuous operation and grease lubrication)
G	

